

Towards Ontological Foundations for Conceptual Modeling: The Unified Foundational Ontology (UFO) Story

Giancarlo Guizzardi^{1,2}, Gerd Wagner³, João Paulo Andrade Almeida¹, Renata S.S. Guizzardi¹

¹Ontology and Conceptual Modeling Research Group (NEMO),
Federal University of Espírito Santo, Vitória, Brazil
{gguizzardi, jpalmeida, rguizzardi}@inf.ufes.br

²Laboratory for Applied Ontology (LOA),
Institute for Cognitive Science and Technology (ISTC)
Italian National Research Council (CNR), Trento, Italy

³Institute of Informatics,
Brandenburg University of Technology, Germany
G.Wagner@tu-cottbus.de

Abstract. This paper describes a long-term research program on developing ontological foundations for conceptual modeling. This program, organized around the theoretical background of the foundational ontology *UFO (Unified Foundational Ontology)*, aims at developing theories, methodologies and engineering tools with the goal of advancing conceptual modeling as a theoretically sound discipline but also one that has concrete and measurable practical implications. The paper describes the historical context in which UFO was conceived, briefly discusses its stratified organization, and reports on a number of applications of this foundational ontology over more than a decade. In particular, it discusses the most successful application of UFO, namely, the development of the conceptual modeling language *OntoUML*. The paper also discusses a number of methodological and computational tools, which have been developed over the years to support the OntoUML community. Examples of these methodological tools include *ontological patterns* and *anti-patterns*; examples of these computational tools include automated support for pattern-based model construction, formal model verification, formal model validation via visual simulation, model verbalization, code generation and anti-pattern detection and rectification. In addition, the paper reports on a variety of applications in which the language as well as its associated tools have been employed to engineer models in several institutional contexts and domains. Finally, it reflects on some of these lessons learned by observing how OntoUML has been actually used in practice by its community and on how these have influenced both the evolution of the language as well as the advancement of some of the core ontological notions in UFO.

1. Introduction

This paper describes a long-term research program on developing ontological foundations for conceptual modeling. This research program aims at developing theories, methodologies and engineering tools (including modeling languages, patterns, anti-patterns as well as computational tools) with the goal of advancing conceptual modeling as a theoretically sound discipline with concrete and measurable practical implications. For over a decade, our research program has been organized around the theoretical background of a foundational ontology termed *UFO (Unified Foundational Ontology)* and, frequently, materialized through the development of number of results associated with an ontologically well-founded conceptual modeling version of UML termed *OntoUML*.

In section 2, we start by briefly describing the historical context in which UFO was conceived. This has the purpose of highlighting the goals of the project and contextualizing the rationale behind fundamental ontological choices made in the design of UFO. In section 3, we briefly discuss the layers (or strata) comprising UFO and the ontological micro-theories comprising each of them. This section also reports on a number of applications of this foundational ontology over more than a decade, chiefly, related to the ontological analysis, (re) design and integration of different modeling languages, reference models and standards. In section 4, we discuss the most successful application of UFO, namely, the development of the OntoUML language. The section briefly discusses the design of this language and reports on a number of applications in which the language as well as its associated methodological and computational tools have been employed to engineer models in a variety of institutional contexts and domains. In addition, the section elaborates on the development of a model-based computational environment, which has been developed to support the OntoUML community in terms of pattern-based model construction, code generation, formal verification, formal validation via visual simulation, model verbalization and anti-pattern detection and rectification. Given the diffusion of the language, over the years, we have managed to assemble a model repository containing

OntoUML models in different domains. The observation of how the language was used in practice in the construction of these models proved to be a fruitful source of empirical knowledge about the actual notions that needed to be accounted for in an ontology-driven structural conceptual modeling language. Section 5 concludes the paper by reflecting on some of these lessons learned and how they have influenced both the evolution of the language of some core ontological notions in UFO.

2. A Brief Historical Background

In 2002, the first two authors have started a research program of conducting ontological analysis of conceptual modeling languages and standards with the goal of developing sound ontological foundations for conceptual modeling languages (Guizzardi et al., 2002a, 2002b). Our program was motivated by the strong belief that any serious scientific discipline should have well-established and explicitly defined metaphysical foundations (Bunge, 1977) or that, as nicely put by (Collier, 1994): *“the opposite of ontology is not non-ontology, but bad ontology”*. In other words, any representation system that has some real-world semantics (as opposed to mere formal semantics) makes an ontological commitment (Guizzardi & Halpin, 2008). This research program was motivated by the belief that controlling and defending a particular ontological commitment is essential for the progress of a scientific discipline.

In the realm of conceptual modeling, the idea that *“data are fragments of a theory of the real-world and data processing is about manipulating models of such a theory”* was there since Mealy’s seminal paper entitled ‘Another Look on Data’ (Mealy, 1967). In fact, Mealy’s paper seems to contain the first mention of the term ‘ontology’ in the computer and information science literature. A number of fundamental conceptual modeling issues of an ontological nature were also discussed in Bill Kent’s book ‘Data and Reality’ (Kent, 1978). This book brought attention to issues like identity, unity and classification, and started exposing the subtleties of fundamental conceptual modeling constructs such as *relationships*.

However, neither Mealy’s paper nor Kent’s book tried to actually develop comprehensive ontological foundations for conceptual modeling. Perhaps the first corpus of work to attempt that goal was reported in the series of publications initiated by Yair Wand, Ron Weber and colleagues (Wand & Weber, 1989, 1990; Weber, 1997) in the late 80’s. Instead of developing a new ontology themselves, Wand and Weber proposed an adaptation of the ontological theory put forth by the Argentinean physicist and philosopher of science Mario Bunge. The result of this effort came to be known as the BWW (Bunge-Wand-Weber) ontology. The authors then employed this theory to evaluate a number of conceptual modeling languages including NIAM (Weber & Zhang, 1991), ER (Wand et al., 1999), UML (Evermann & Weber, 2001) and OWL (Bera & Wand, 2004).

Despite being inspired by the goals of the BWW approach, we did not share their research direction. Bunge’s objective was doing philosophy of science and, being a physicist, chiefly, philosophy of the hard sciences. Conceptual Modeling, in contrast, is about *“representing aspects of the physical and social world for the purpose of understanding and communication [and, hence] the contribution of a conceptual modeling notation rests in its ability to promote understanding about the depicted reality among human users”* (Mylopoulos, 1992). As a result, any attempt to develop ontological foundations for conceptual modeling should take both human cognition and human linguistic competence seriously; it should be a project in descriptive metaphysics and not in revisionary ontology (Guarino & Guizzardi, 2006; Guizzardi, 2007b). This mismatch between the purposes for which Bunge’s ontology was developed and the requirements of ontological foundations for conceptual modeling became manifest in the literature as the predictions made by the BWW approach found themselves in strong contrast with the intuitions and practical knowledge of modelers and with some predictions unanimously shared by alternative approaches. For instance, around 2003, a number of authors showed that the BWW dictum that *“mutual properties (or relations) should never be modeled as classes as they should not be allowed to have properties”* was in conflict with modeling predictions made by other foundational theories (e.g., Jackendoff’s Semantic Structures (Veres & Hitchman, 2002; Veres & Mansson, 2005)) and with the intuition of modelers. Regarding the latter, as shown by (Hitchman, 2003), in recorded modeling sessions with practitioners, it became evident that reified relationships were frequently a part of these practitioners’ ontology.

It was clear to us from the outset that we needed an ontological theory that would countenance both individuals and universals and one that would include not only substantial individuals and universals but also accidents (particularized properties, moments, qualities, modes, tropes, abstract particulars, aspects, ways) and accident universals. In other words, we needed a *Four-Category Ontology* (Lowe, 2006). We needed particularized properties not only because they were of great importance in making sense of language and cognition (Davison, 2001; Parsons, 1990; Masolo et al., 2003) but because they

would repeatedly appear in the discourse of conceptual modelers. As previously mentioned, particularized relations (relationships) and particularized intrinsic properties (e.g., often represented by the so-called weak entities) are frequently modeled as bearers of other particularized properties in the practice of conceptual modeling. In fact, as demonstrated by (Guizzardi, 2005; Guizzardi et al., 2006; Guizzardi & Wagner, 2008; Guarino & Guizzardi, 2015), there are many conceptual modeling problems that can hardly be solved without considering particularized properties.

In initial papers for this project, we attempted to employ the GFO (General Formalized Ontology)/GOL (General Ontology Language) being developed in Leipzig, Germany, as our reference theory (Heller & Herre, 2004; Heller et al., 2004). More or less at the same time, a strong cooperation was established with the Laboratory of Applied Ontology (LOA) (Trento, Italy), which was during that period developing the Descriptive Ontology for Linguistic and Cognitive Engineering (DOLCE) (Masolo et al., 2003). In this setting, our first attempt was to unify DOLCE and GFO to produce a reference foundational ontology for conceptual modeling (hence, the name *Unified Foundational Ontology*) (Guizzardi & Wagner, 2004). Both theories were philosophically sound and formally characterized. Moreover, they were both based on the so-called Aristotelian Square, i.e., “Four-Category Ontologies”.

It became clear quite soon, however, that further investigation was needed, with a focus on the requirements of the conceptual modeling discipline. In particular, ontological foundations for conceptual modeling would demand micro-theories to address conceptual modeling’s most fundamental constructs, namely, *Entity Types* and *Relationship Types* (hence, the name of the so-called Entity-Relationship approach that gives the name to the most important conference in conceptual modeling!). So, any reference theory for conceptual modeling would need a rich theory of entity (object) types and a rich theory of domain (also called material) relations. In the case of the former, we needed something in the spirit of the ontology of universals underlying the OntoClean methodology (Guarino & Welty, 2009) in order to systematize a number of notions that were pervasive in the conceptual modeling literature (e.g., types, roles, phases or states, mixins) but for which there were no precise definitions or consensus (Guizzardi et al., 2004a). In that respect, GFO’s theory of universals still does not recognize these notions and DOLCE does not include universal as a category (DOLCE was designed as an ontology of particulars). Regarding the latter, DOLCE still does not include a theory of particularized relational properties (relational qualities) and the GFO theory of relations is subject to the so-called Bradley Regress (Bradley, 1893) and, hence, it can only be instantiated by infinite (logical) models. This feature makes it unsuitable for conceptual modeling applications. Finally, there were many additional specific aspects needed for a general ontology for conceptual modeling that were not addressed by the existing approaches (e.g., attributes and datatypes, different types of specialization relations between relations, a rich theory of cognitively/linguistically motivated part-whole relations). We needed to develop a full-blown foundational ontology specifically created to address these conceptual modeling requirements.

3. The Unified Foundational Ontology and its applications

The UFO ontology was developed by consistently putting together a number of theories originating from areas such as Formal Ontology in philosophy, cognitive science, linguistics and philosophical logics. It comprises a number of micro-theories addressing fundamental conceptual modeling notions. The ontology is divided in three strata dealing with different aspects of reality, namely:

- **UFO-A:** An Ontology of Endurants dealing with aspects of structural conceptual modeling. It is organized as a Four-Category ontology comprising theories of Types and Taxonomic Structures (Guizzardi et al., 2004a; Guizzardi, 2012) connected to a theory of object identifiers (including a formal semantics in a Sortal Quantified Modal Logics (Guizzardi, 2015)), Part-Whole Relations (Guizzardi, 2007a, 2009, 2010a, 2011), Particularized Intrinsic Properties, Attributes and Attribute Value Spaces (Guizzardi et al., 2004b, 2006; Guizzardi & Zamborlini, 2014) (including a theory of Datatypes as Measure Structures (Albuquerque & Guizzardi, 2013)), Particularized Relational Properties and Relations (Guizzardi & Wagner, 2008; Costal et al., 2011; Guarino & Guizzardi, 2015) and Roles (Guizzardi, 2006; Masolo et al., 2005);
- **UFO-B:** An Ontology of Perdurants (Events, Processes) dealing with aspects such as Perdurant Mereology, Temporal Ordering of Perdurants, Object Participation in Perdurants, Causation, Change and the connection between Perdurants and Endurants via Dispositions (Guizzardi et al., 2013a);

- **UFO-C:** An Ontology of Intentional and Social Entities, which is constructed on top of UFO-A and UFO-B, and which addresses notions such as Beliefs, Desires, Intentions, Goals, Actions, Commitments and Claims, Social Roles and Social Particularized Relational Complexes (Social Relators), among others (Guizzardi et al., 2008; Guizzardi & Guizzardi, 2010).

Over the years, UFO has been employed as a basis for analyzing, reengineering and integrating many modeling languages and standards in different domains (e.g., UML, TOGAF, ArchiMate, RM-ODP, TROPOS/i*, AORML, ARIS, BPMN) as well as for the development of Core and Domain Ontologies in different areas. For instance, it has been successfully used to provide conceptual clarification in complex domains such as Services (Nardi et al., 2015), Capabilities (Azevedo et al., 2015), Organizational Structures (Santos Junior et al., 2013), Communities (Almeida & Guizzardi, 2013), Goals and Motivations (Guizzardi et al., 2012, 2013b; Azevedo et al., 2011), Constitutional Law (Griffo et al., 2015), Business Processes (Guizzardi & Wagner, 2011b; Santos Junior et al., 2010), Discrete Event Simulation (Guizzardi & Wagner, 2010, 2011a, 2012, 2013), Simulation for Land Covering and Use (Grueau, 2013), Software Quality (Shekhovtsov & Mayr, 2014), Software Measurement (Moretto & Barcellos, 2013), Foundations of Software Engineering (Henderson-Sellers, 2012; Henderson-Sellers et al., 2014), Software Requirements (Guizzardi et al., 2014), among many others. Of all applications of UFO, one deserves special attention, namely, the use of UFO-A in the design of an ontology-driven conceptual modeling language, which later came to be known as OntoUML. This language is discussed in the next section.

4. OntoUML: Language, Engineering Support and its Applications

OntoUML (Guizzardi, 2005) was conceived as an ontologically well-founded version of the UML 2.0 fragment of class diagrams. The idea was to employ the ontology-based language engineering method proposed by (Guizzardi et al., 2005) (and later refined by (Guizzardi, 2013)) to design a *language for structural conceptual modeling* (i.e., for modeling aspects related to endurants) that would have two main characteristics. Firstly, the worldview embedded in the language through its conceptual primitives (what some authors would call the *ontology behind the language* (Guizzardi, 2007b)) should be isomorphic to the ontological distinctions put forth by UFO-A. Secondly, the language metamodel should incorporate formal syntactical constraints that would delimit the set of grammatically valid models of the language to those that represented intended state of affairs admitted by the underlying ontology. By doing this, we have managed to build a modeling language with explicitly defined formal and real-world semantics. This language serves as an engineering tool for enabling the use of formal ontological theories in the construction of conceptual models and domain ontologies.

Over the years, OntoUML has been adopted by many research, industrial and government institutions worldwide. In particular, it has been considered as a candidate for addressing the OMG SIMF (Semantic Information Model Federation) Request for Proposal¹, after a report of its successful use over the years by a branch of the U.S. Department of Defense (2011). In addition, some of the foundational theories underlying OntoUML have also been adopted by other conceptual modeling languages, e.g., ORM 2.0 (Halpin & Morgan, 2008; Halpin, 2010). It has been employed in a number of projects in different countries, in academic, government and industrial institutions, in domains such as Geology (Carbonera et al., 2015; Abel et al., 2015), Biodiversity Management (Albuquerque et al., 2015), Organ Donation (Pereira et al., 2015), Petroleum Reservoir Modeling (Werlang, 2015), Disaster Management (Moreira et al., 2015), Context Modeling (Brandt et al., 2014), Datawarehousing (Moreira et al., 2014), University Campus Management (Carolla & Spitta, 2014), Enterprise Architecture (Buckl et al., 2011), Metamodeling (Nijenhuis, 2011), Data Provenance (Serra, 2012), Measurement (Nunes et al., 2015), Logistics (Andreeva et al., 2015), Integration of Analytical Tools (Blackburn & Denno, 2015), Complex Media Management (Carolo & Burlamaqui, 2011), Telecommunications (Barcelos et al., 2011), Petroleum and Gas (Guizzardi et al., 2010), heart electrophysiology (Gonçalves et al., 2011), among many others.

The decision to build the language as a version of UML (technically, as a UML profile) was mainly motivated by the fact that UML (unlike many other conceptual modeling languages) has a standardized and explicitly defined metamodel and a significant set of metamodeling tools that can be used to manipulate and extend this metamodel. As a result, we managed to actually propose a concrete modeling language that could be used to create ontology-driven conceptual models and domain

¹<http://www.omgwiki.org/architecture-ecosystem/>

ontology in a variety of existing UML tools. For instance, as reported by (Guerson et al., 2015), an OntoUML plug-in has been implemented for the professional tool Enterprise Architect². Moreover, as UML is a de facto modeling standard, we also managed to leverage existing knowledge and acceptance of the language (at least among computer scientists).

The first version of this adapted UML metamodel was proposed by (Guizzardi, 2005), fully implemented as a concrete UML profile by (Carraretto, 2010) and implemented as a model-based tool by (Benevides & Guizzardi, 2009). In that original OntoUML editor, we had support for model construction and formal verification (against formal metamodel constraints reflecting part of the UFO-A axiomatization). Over the years, a number of contributions have been aggregated in the proposal of a new editor that, besides supporting model construction and formal verification, incorporates support for a number of additional methodological features (Guerson et al., 2015):

- (i) **A Pattern-Based approach for Model Construction:** As demonstrated by (Guizzardi et al., 2011; Guizzardi, 2014), OntoUML is actually a Pattern-Based Language in the sense that its modeling primitives are *patterns*, i.e., higher-granularity clusters of modeling elements that can appear in a model only in particular fixed configurations. Moreover, these patterns are of an ontological nature, as they directly reflect the ontological micro-theories underlying the language. Examples include the *role with disjoint allowed types* modeling pattern proposed by (Guizzardi et al., 2004a), the *relator-material relation* pattern (Guizzardi & Wagner, 2008), the *qualities with alternative quality spaces* pattern (Guizzardi et al., 2006), among many others. Furthermore, the editor also implements a number of topological patterns that allows for isolating the scope of transitivity of part-whole relations (Guizzardi, 2009). Finally, the editor allows for the extraction of *Domain-Related Patterns* from Core Ontologies (e.g., the *Employment*, *Organization Structure* and *Project Involvement* patterns exemplified by (Ruy et al., 2015)) such that these patterns can be reused for the construction of Domain Ontologies;
- (ii) **Model Verbalization:** Model verbalization stands for the activity of generating a rendering of the model in (controlled) natural language. This process is very useful, for example, to allow domain experts that are not well-versed in the modeling language's notation, to access a partial view of what is represented in a conceptual model. The editor incorporates a functionality for automatically generating model verbalization in structured English following a slightly modified version of the *SBVR (Semantics for Business Vocabularies and Rules)* OMG proposal³;
- (iii) **Support for the Representation of Domain-Specific Formal Constraints:** In order to cover domain constraints that cannot be represented using the language's diagrammatic notation, the current editor supports the specification of OCL (Guerson et al., 2014) and temporal OCL formal constraints (Guerson & Almeida, 2015). The editor provides support for syntax highlighting, code-completion and syntax verification (parsing) for textual constraints;
- (iv) **Model Validation:** This approach addresses conceptual model validation by using *visual simulation*. In particular, in the strategy proposed by (Benevides et al., 2010; Braga et al., 2010) and implemented in this later version of the editor, we have the automatic generation of visual instances (exemplars) of a given conceptual model such that the modeler can be confronted with what her model is actually representing. In other words, the strategy is to systematically contrast the set of formally-valid instances of a given conceptual model (automatically generated by the visual simulator) with the set of *intended* instances of that model (i.e., instances that represent admissible state of affairs in reality), which exists only in the modeler's mind. Once the modeler detects a deviation between valid and intended instances (either due to *overconstraining* or *underconstraining* of the model), she rectifies the model, for instance, by the inclusion of formal domain-specific constraints;

²<http://www.sparxsystems.com.au/>

³<http://www.omg.org/spec/SBVR/1.2/>

- (v) **Ontology Codification:** In the ontology engineering process defended by (Guizzardi, 2007b; Guizzardi & Halpin, 2008; Guizzardi, 2010b), we have advocated a separation between the modeling approaches that should be used for the conceptual modeling phase of ontology engineering and the representation approaches that could be used to realize alternative implementations of a given ontology (as a conceptual model). For instance, given a conceptual model representing a domain ontology in OntoUML, we can have different mappings to different codification languages (e.g., OWL DL, RDFS, F-Logic, Haskell, Relational Database languages, CASL, among many others). The choice of each of these languages should be made to favor a specific set of non-functional requirements. Moreover, within the solution space defined by these codification languages, we have a multitude of choices regarding, for instance, decidability, completeness, computational complexity, reasoning paradigm (e.g., closed versus open world, adoption of a unique name assumption or not), expressivity (e.g., regarding the need for representing modal constraints, higher-order types, relations of a higher arity), verification of finite satisfiability, among many others. In the current version of the editor, we have implemented six different automatic mappings from OntoUML to OWL contemplating different transformation styles that were designed to address different sets of non-functional requirements (Guizzardi & Zamborlini, 2014, Zamborlini & Guizzardi, 2010). It is important to highlight that other authors have implemented alternative mappings from OntoUML to languages such as XML (Baumann, 2009), Smalltalk (Pergl et al., 2013), OWL (Barcelos et al., 2013) and a version of a Modal Prolog (Araujo, 2015);

- (vi) **Anti-Pattern Detection and Rectification:** Given the diffusion of the language, we have managed to assemble a model repository containing OntoUML models in different domains (e.g., telecommunications, government, biodiversity, bioinformatics), different sizes (e.g., ranging from dozens of concepts to thousand of concepts), and produced in different types of contexts (e.g., ranging from academic exercises of novices to models produced by teams of practitioners in industrial or government settings) (Sales & Guizzardi, 2015). By using this model repository as a benchmark, in three different empirical studies, (Guizzardi & Sales, 2014; Sales & Guizzardi, 2015) managed to show that this approach for model validation via visual simulation is not only able to detect deviations between formally valid model instances and intended model instances, but is also able to detect recurrent structures that tend to cause these deviations, i.e., *ontological anti-patterns*. Once these anti-patterns are catalogued, they were able to devise solution patterns, i.e., solution proposals that eliminate the deviation between valid instances and intended instances (Guizzardi & Sales, 2014; Sales & Guizzardi, 2015). The current version of the editor implements both a mechanism for anti-pattern detection and an implementation of these proposed rectification solutions. Sales and Guizzardi (2015) have presented a validation study developed with a large industrial model and managed to empirically demonstrate, for the vast majority of the identified anti-patterns, a very high correlation between the presence of these anti-patterns and the adoption of our proposed solutions for ontology-based model enhancement.

5. Learning from “*Systematic Language Subversions*” to evolve UFO and OntoUML

The observation of the application of OntoUML over the years conducted by a variety of groups in a variety of domains also amounted to a very fruitful empirical source of knowledge for us regarding the language and its foundations. In particular, we have managed to observe a number of different ways in which people would slightly *subvert* the syntax of the language, ultimately creating what we could call “*systematic subversions*” of the language. These “subversions” would (purposefully) produce models that were grammatically incorrect, but which were needed to express the intended characterization of their underlying conceptualizations that could not be expressed otherwise. Loosely speaking, following the semiotic engineering principle of seeing representations as dialogues between designer and user (de Souza, 2005), we had the feeling that the users of the language were “speaking to us” via these “systematic subversions”.

One example is the representation of events in OntoUML models. As previously mentioned, the language was created to represent structural conceptual models expressing endurantistic aspects of reality. However, systematically, a number of authors, in different institutions and in different domains (e.g., Moretto & Barcellos, 2013; U.S. Department of Defense, 2011) started to produce OntoUML models in which perdurants (and perdurant relations) would appear as modeling primitives. These

examples were concrete cases of the need to also represent perdurants in structural conceptual models (Olivé, 2007). In order to respond to these modeling requirements, we intend to, once more, employ the aforementioned ontology-based language engineering process, extending the metamodel the language to incorporate the ontological distinctions and axiomatization prescribed by UFO-B (Guizzardi et al., 2013a). Doing that, however, requires that a number of new research problems be addressed. To cite one of these challenges, given that the introduction of this new perspective substantially increases the complexity of the resulting diagrams, new complexity management theories and tools for OntoUML diagrams need to be developed (e.g., dealing with model filtering, modularization, viewpoint selection).

A second case systematic “language subversions” led us to reconsider some of the theoretical foundations underlying the language, i.e., it led us to rethink and evolve a core theory in UFO. As previously mentioned, in the original version of UFO (and, hence, also in OntoUML), we had a number of ontological distinctions representing different sorts of universals. These include distinctions between substance sortals (kinds), phased-sortals (roles and phases) and non-sortals (categories, mixins and role mixins). These distinctions, however, were considered to be distinctions among *object universals*. However, consciously ignoring this rule, users of the language started to systematically employ these distinctions also when characterizing universals whose instances are *existentially dependent endurants* (i.e., moments/aspects/particularized properties such as modes and relators). These “subversions” called our attention to the fact that, like full-fledged endurants, modes and relators also have their identity supplied by substance sortals (i.e., mode kinds and relator kinds) and are also subject of both essential and accidental properties. If these endurants can be subjects of modal properties, then they can also contingently instantiate anti-rigid types. In other words, phases, roles, roleMixins, mixins, categories, etc., (as sorts of types characterized by formal ontological meta-properties) could also be used to characterize mode and relator universals. This realization triggered a process that led to a much richer theory of material relations and particularized relational properties in UFO, which in turn triggered an evolution of the OntoUML model, with direct interesting consequences to the practice of conceptual modeling (Guarino & Guizzardi, 2015). In fact, in an upcoming version of UFO, these different sorts of universals will be applicable to all categories of endurant universals, including the so-called *powertypes*. Powertypes can be loosely defined as “types whose instances are other types” (e.g., the type *Organization Position*, which can be instantiated by the types *Director*, *Manager* and *Secretary*, or the type *Bird Species*, which can be instantiated by the types *Golden Eagle* and *Emperor Penguin*). (Guizzardi et al., 2015) defend that powertypes should not be interpreted as higher-order universals but as concrete *resemblance structures* (Armstrong, 1990) that are themselves *endurants*.

With the increasing popularization of OntoUML and its associated tools, this dialogue with language users will continue, with more implications to be drawn to OntoUML and UFO from their practical applications in various domains. In this way, the evolution of the language and its conceptual foundations can remain anchored in the conceptual modeling discipline, not only taking the real-world semantics of conceptual modeling primitives seriously, but also addressing recurrent conceptual modeling problems against the solid background of formal ontology. We believe this combined use of insights from theory and practice is key to applied ontology in general, but is essential to ontology-driven conceptual modeling.

Acknowledgements. The authors are grateful to Ricardo Falbo, Monalessa Barcellos, Nicola Guarino, John Mylopoulos, Heinrich Herre and the members of NEMO for many years of fruitful collaboration. Finally, we would like to express our gratitude to Terry Hapin, Alex Borgida and Yair Wand for their valuable comments to a previous version of this paper.

References

1. Abel, M., Perrin, M., Carbonera, J.L. (2015): Ontological analysis for information integration in geomodeling, *Earth Science Informatics*, 8(1).
2. Albuquerque, A., Guizzardi, G. (2013): An ontological foundation for conceptual modeling datatypes based on semantic reference spaces, in: 7th IEEE International Conference on Research, Challenges in Information Science (RCIS 2013), Paris, ISBN 978-1-4673-2912-5, pp. 1–12.
3. Albuquerque, A.C.F., Campos dos Santos, J.L.; De Castro, A.N., *OntoBio* (2015): A Biodiversity Domain Ontology for Amazonian Biological Collected Objects, 48th Hawaii International Conference on System Sciences (HICSS).
4. Almeida, J.P.A., Guizzardi, G. (2013): An Ontological Analysis of the Notion of Community in the RM-ODP Enterprise Language, Standards & Interfaces, doi: 10.1016/j.csi.2012.01.007.
5. Andreeva, E., et al. (2015): One Solution for Semantic Data Integration in Logistics, Enterprise and Organizational Modeling and Simulation Volume 231 of the series Lecture Notes in Business

Information Processing pp 75-86.

6. Araujo, L.C. (2015): An Ontology-Based Language to Formalize Discourses, PhD Thesis, University of Brasilia, Brazil, 2015.
7. Armstrong, D.M., A Theory of Universals, Vol. 2: Universals and Scientific Realism, Cambridge University Press, 1990.
8. Azevedo, C., Jacob, M.E., Almeida, J.P., Pires, L.F., Guizzardi, G. (2015): Modeling Resources and Capabilities in Enterprise Architecture: A Well-Founded Ontology-Based Proposal for ArchiMate, Information Systems, Oxford University Press.
9. Azevedo, C.; Almeida, J.P.A., van Sinderen, M.J., Quartel, D., Guizzardi, G. (2011): An Ontology-Based Semantics for the Motivation Extension to ArchiMate, 15th IEEE International Conference on Enterprise Computing (EDOC 2011), Helsinki, Finland.
10. B. Henderson-Sellers (2012):, On the Mathematics of Modelling, Metamodeling, Ontologies and Modelling Languages, Springer Briefs in Computer Science, Springer-Verlag, Heidelberg, 106 pp.
11. Barcelos, P.P.F., Santos, V. A. dos, Silva, F.B., Monteiro M.E., Garcia A.S. (2013): "An Automated Transformation from OntoUML to OWL and SWRL", Ontobras, pp. 130-141.
12. Barcelos, P.P.F.; Guizzardi, G.; Garcia, A.S., Monteiro, M.E. (2011): Ontological Evaluation of the ITU-T Recommendation G.805, 18th International Conference on Telecommunications (ICT 2011), IEEE Press, Cyprus
13. Bauman, B.T. (2009): Prying apart semantics and implementation: generating XML schemata directly from ontologically sound conceptual models, in: Balisage Markup Conference.
14. Benevides, A.B. et al. (2010): Validating Modal Aspects of OntoUML Conceptual Models Using Automatically Generated Visual World Structures. Journal of Universal Computer Science. 16, 2904–2933.
15. Benevides, A.B., Guizzardi, G. (2009):: A Model-Based Tool for Conceptual Modeling and Domain Ontology Engineering in OntoUML, 11th International Conf. on Enterprise Information Systems (ICEIS), Milan.
16. Bera, P. & Wand, Y. (2004): Analyzing OWL using a philosophy-based ontology. In Formal Ontology in Information Systems. Amsterdam: IOS Press.
17. Blackburn, M.A., Denno, P.O. (2015): Using Semantic Web Technologies for Integrating Domain Specific Modeling and Analytical Tools, Complex Adaptive Systems San Jose, CA November 2-4, Elsevier.
18. Bradley, F.H. (1893): Apperance and Reality, George Allen & Unwin Ltd., London.
19. Braga, B., Almeida, J.P.A., Guizzardi, G.; Benevides, A.B. (2010): Transforming OntoUML into Alloy: Towards Conceptual Model Validation using a Lightweight Formal Method, Innovations in System and Software Engineering (ISSE), Springer-Verlag.
20. Brandt, P., Basten, T., Stuijk, S. (2014): ContoExam: an ontology on context-aware examinations, 8th International Conference on Formal Ontology in Information Systems (FOIS 2014), Rio de Janeiro, Brazil.
21. Buckl, S., Matthes, F., Schweda, C.M., (2011): A method to develop EA modeling languages using practice-proven solutions, ADVANCES IN ENTERPRISE ENGINEERING V, Lecture Notes in Business Information Processing, Volume 79.
22. Bunge M. (1977): Treatise on Basic Philosophy. Vol. 3. Ontology I. The Furniture of the World. D. Reidel Publishing, New York.
23. Carbonera, J., Abel, M., Scherer, C.M.S. (2015): Visual interpretation of events in petroleum exploration: An approach supported by well-founded ontologies, Expert Systems with Applications, Volume 42, Issue 5, Pages 2749–2763.
24. Carolla, M., Spitta, T. (2014): Methodological Aspects of a Data Reference Model for Campus Management Systems, Fakultät für Wirtschaftswissenschaften, Technical Report, University of Bielefeld.
25. Carolo, F., Burlamaqui, L. (2011): Improving Web Content Management with Semantic Technologies, Semantic Technology Conference (SemTech), San Francisco.
26. Carraretto, R. (2010): A Modeling Infrastructure for OntoUML", Technical Report, Ontology and Conceptual Modeling Research Group (NEMO), Federal University of Espirito Santo, Brazil.
27. Collier, A. (1994): Critical Realism: An Introduction to Roy Bhaskar's Philosophy. London, England: Verso.
28. Costal, D., Gómez, C., Guizzardi, G. (2011): Formal Semantics and Ontological Analysis for Understanding Subsetting, Specialization and Redefinition of Associations in UML, 30th International Conference on Conceptual Modeling (ER 2011), Brussels, Belgium.
29. D. Davidson (2001): The logical form of action sentences, in: Essays on Actions and Events, Oxford University Press, ISBN 9780199246274.
30. De Souza, C. S. (2005): The Semiotic Engineering of Human-Computer Interaction, MIT Press, 2005.
31. E.J. Lowe (2006): The Four Category Ontology, Oxford University Press.
32. Evermann, J. and Wand, Y. (2001): Towards ontologically based semantics for UML constructs. In H. Kunii, S. Jajodia, and A. Solvberg, editors, Proceedings of the 20th International Conference on Conceptual Modeling (ER), Japan.
33. Gonçalves, B.N.; Guizzardi, G.; Pereira Filho, J.G. (2011): Using an ECG reference ontology for semantic interoperability of ECG data, Journal of Biomedical Informatics, Special Issue on Ontologies for Clinical

- and Translational Research, Editors: Barry Smith, Werner Ceusters and Richard H. Scheuermann, Elsevier.
34. Griffo, C., Almeida, J.P.A., Guizzardi, G. (2015): Towards A Legal Core Ontology Based on Alexy's Theory of Fundamental Rights, ICAIL Multi-Lingual Workshop on AI & Law (MMAIL 2015), 15th International Conference on Artificial Intelligence and Law (ICAIL 2015), San Diego.
 35. Grueau Grueau, C. (2013): Towards a Domain Specific Modeling Language for Agent-Based Modeling of Land Use/Cover Change, Advances in Conceptual Modeling, Lecture Notes in Computer Science Volume 8697, 2014, pp 267-276.
 36. Guarino, N., Guizzardi, G. (2015): "We need to Discuss the Relationship": Revisiting Relationships as Modeling Constructs, 27th International Conference on Advanced Information Systems Engineering (CAISE 2015), Stockholm.
 37. Guarino, N.; Guizzardi, G. (2006): In the Defense of Ontological Foundations for Conceptual Modeling, Scandinavian Journal of Information Systems, Vol.18, No. 1, ISSN 0905-0167, 2006.
 38. Guarino, N.; Welty, C. (2009): An Overview of OntoClean, in S. Staab, R. Studer (eds.), Handbook on Ontologies, Springer-Verlag, 2nd Edition, pp. 201-220.
 39. Guerson, J., Almeida, J. P. A. (2015): Representing Dynamic Invariants in Ontologically Well-Founded Conceptual Models", In 20th International Conference, EMMSAD.
 40. Guerson, J., Almeida, J.P.A., Guizzardi, G. (2014): Support for Domain Constraints in Ontologically Well-Founded Conceptual Models, 19th International Conference on Exploring Modeling Methods for Systems Analysis and Design (EMMSAD 2014), Thessaloniki, Greece.
 41. Guerson, J., Sales, T.P., Guizzardi, G., Almeida, J.P.A. (2015): OntoUML Lightweight Editor: A Model-Based Environment to Build, Evaluate and Implement Reference Ontologies, 19th IEEE Enterprise Computing Conference (EDOC 2015), Demo Track, Adelaide, Australia.
 42. Guizzardi, G. (2005): Ontological Foundations for Structural Conceptual Models, Telematics Instituut Fundamental Research Series, No. 015, ISSN 1388-1795, The Netherlands.
 43. Guizzardi, G. (2006): Agent Roles, Qua Individuals and The Counting Problem, Invited Chapter in Software Engineering of Multi-Agent Systems, vol. IV, P. Giorgini, A.Garcia, C. Lucena, R. Choren (eds.), Springer-Verlag, 2006.
 44. Guizzardi, G. (2007a): Modal aspects of object types and part-whole relations and the de re/de dicto distinction. In 19th International Conference on Advanced Information Systems Engineering (CAISE'07), Trondheim. Lecture Notes in Computer Science, Vol. 4495. Springer-Verlag.
 45. Guizzardi, G. (2007b): On Ontology, ontologies, Conceptualizations, Modeling Languages, and (Meta)Models, Frontiers in Artificial Intelligence and Applications, Databases and Information Systems IV, IOS Press, Amsterdam.
 46. Guizzardi, G. (2009): The Problem of Transitivity of Part-Whole Relations in Conceptual Modeling Revisited, 21st Intl. Conf. on Advanced Information Systems Engineering (CAISE'09), The Netherlands.
 47. Guizzardi, G. (2010a): On the Representation of Quantities and their Parts in Conceptual Modeling, 6th International Conf. on Formal Ontology and Information Systems (FOIS'10), Toronto, Canada.
 48. Guizzardi, G. (2010b): Theoretical Foundations and Engineering Tools for Building Ontologies as Reference Conceptual Models, Semantic Web Journal, Editors-in-Chief: Pascal Hitzler and Krzysztof Janowicz, IOS Press, Amsterdam.
 49. Guizzardi, G. (2011): Ontological Foundations for Conceptual Part-Whole Relations: The Case of Collectives and their Parts, 23rd International Conference on Advanced Information System Engineering (CAISE'11), London, UK.
 50. Guizzardi, G. (2012): Ontological Meta-Properties of Derived Object Types, 24th International Conference on Advanced Information System Engineering (CAISE'12), Gdansk, Poland.
 51. Guizzardi, G. (2013): Ontology-Based Evaluation and Design of Visual Conceptual Modeling Languages. In: Reinhartz-Berger, I., Sturm, A., Clark, T., Cohen, S., Bettin, J. (eds.) Domain Engineering. Product Lines, Languages and Conceptual Models, p. 345. Springer, New York (2013)
 52. Guizzardi, G. (2014): Ontological Patterns, Anti-Patterns and Pattern Languages for Next-Generation Conceptual Modeling, Conceptual Modeling (ER 2014), Atlanta, USA.
 53. Guizzardi, G. (2015): Logical, Ontological and Cognitive Aspects of Objects Types and Cross-World Identity with applications to the theory of Conceptual Spaces, Applications of Conceptual Space: The Case for Geometric Knowledge Representation, Peter Gardenfors and Frank Zenker (Editors), Synthese Library, Dordrecht, Springer.
 54. Guizzardi, G. et al. (2006): In the Defense of a Trope-Based Ontology for Conceptual Modeling: An Example with the Foundations of Attributes, Weak Entities and Datatypes, 25th International Conference on Conceptual Modeling (ER'2006), Tucson.
 55. Guizzardi, G. et al. (2011): Design Patterns and Inductive Modeling Rules to Support the Construction of Ontologically Well-Founded Conceptual Models in OntoUML, 3rd International Workshop on Ontology-Driven Information Systems (ODISE 2011), London, UK.
 56. Guizzardi, G. et al. (2013a): Towards Ontological Foundations for the Conceptual Modeling of Events, 32nd International Conf. on Conceptual Modeling (ER 2013), Hong Kong, 2013.
 57. Guizzardi, G., Almeida, J.P.A., Guarino, N., Carvalho, V.A. (2015): Towards an Ontological Analysis of Powertypes, International Workshop on Formal Ontologies for Artificial Intelligence (FOFAI 2015), 24th International Joint Conference on Artificial Intelligence (IJCAI 2015), Buenos Aires.

58. Guizzardi, G., Falbo, R. A., Guizzardi, R. S. S. (2008): Grounding Software Domain Ontologies in the Unified Foundational Ontology (UFO): The case of the ODE Software Process Ontology, 11th Iberoamerican Conference on Software Engineering (CIBSE 2008), Recife.
59. Guizzardi, G., Halpin, T. (2008): Ontological Foundations for Conceptual Modeling. *Applied Ontology*, v.3, p.91 - 110.
60. Guizzardi, G., Herre, H., Wagner G. (2002a): On the General Ontological Foundations of Conceptual Modeling, 21st International Conf. on Conceptual Modeling (ER 2002), Tampere.
61. Guizzardi, G., Herre, H., Wagner G. (2002b): Towards Ontological Foundations for UML Conceptual Models. 1st International Conference on Ontologies Databases and Applications of Semantics (ODBASE), USA.
62. Guizzardi, G., Lopes, M., Baião, F., Falbo, R. (2010): The role of foundational ontologies for domain ontology engineering: an industrial case study in the domain of oil and gas exploration and production, *International Journal of Information Systems Modeling and Design*, ISSN 1947-8186.
63. Guizzardi, G., Sales, T. P. (2014): Detection, Simulation and Elimination of Semantic Anti-Patterns in Ontology-Driven Conceptual Models. Proc. of 33rd International Conf. on Conceptual Modeling (ER 2014), Atlanta.
64. Guizzardi, G., Wagner G., Guarino, N., van Sinderen, M. (2004a): An Ontologically well-Founded Profile for UML Conceptual Models, 16th International Conference on Advanced Information Systems Engineering (CAiSE), Latvia.
65. Guizzardi, G., Wagner G., Herre, H. (2004b): On the Foundations of UML as an Ontology Representation Language. In *Proceedings of 14th International Conference on Knowledge Engineering and Knowledge Management (EKAW)*, Springer-Verlag, Berlin, Lecture Notes in Computer Science.
66. Guizzardi, G., Wagner, G. (2008): What's in a relationship: an ontological analysis, *Conceptual Modeling (ER 2008)*, Barcelona, Spain, in: LNCS 5231, 2008, pp. 83–97.
67. Guizzardi, G., Wagner, G. (2010): Towards and Ontological Foundation of Discrete Event Simulation, 16th International Winter Simulation Conference, Baltimore, USA, 2010.
68. Guizzardi, G., Wagner, G. (2011a): Towards and Ontological Foundation of Agent-Based Simulation, 17th International Winter Simulation Conference (WSC 2011), Phoenix, USA.
69. Guizzardi, G., Wagner, G. (2011b) Can BPMN be used for Simulation Models?, 7th International Workshop on Enterprise & Organizational Modeling and Simulation (EOMAS 2011), together with the 23rd International Conference on Advanced Information System Engineering (CAiSE'11), London, UK.
70. Guizzardi, G., Wagner, G. (2012): Conceptual Simulation Modeling with OntoUML, *Proceedings of the 2012 Winter Simulation Conference*, Berlin, Germany.
71. Guizzardi, G., Wagner, G. (2013): Disposition and Causal Laws as the Ontological Foundation of Transition Rules in Simulation Models, *Proceedings of the 2013 Winter Simulation Conference*, Washington DC, USA.
72. Guizzardi, G., Zamborlini, V. (2014): Using a Trope-Based Foundational Ontology for Bridging different areas of concern in Ontology-Driven Conceptual Modeling, *Science of Computer Programming*.
73. Guizzardi, G.; Ferreira Pires, L.; van Sinderen, M. (2005): An Ontology-Based Approach for Evaluating the Domain Appropriateness and Comprehensibility Appropriateness of Modeling Languages, *ACM/IEEE 8th International Conference on Model Driven Engineering Languages and Systems*, Montego Bay, Jamaica, Lecture Notes in Computer Science LNCS 3713, Springer-Verlag.
74. Guizzardi, G.; Wagner, G. (2004): On A Unified Foundational Ontology and some Applications of it in Business Modeling, *Open INTEROP Workshop on Enterprise Modelling and Ontologies for Interoperability*, 16th International Conference on Advances in Information Systems Engineering (CAiSE), Latvia.
75. Guizzardi, R., Li, F-L, Borgida, A., Guizzardi, G., Horkoff, J., Mylopoulos, J. (2014): An Ontological Interpretation of Non-Functional Requirements, 8th International Conference on Formal Ontology in Information Systems (FOIS 2014), Rio de Janeiro, Brazil.
76. Guizzardi, R.S.S., Franch, X., Guizzardi, G. (2012): Applying a Foundational Ontology to Analyze the i* Framework, 6th International Conference on Research Challenges in Information Systems (RCIS 2012), Valencia, Spain.
77. Guizzardi, R.S.S., Franch, X., Guizzardi, G., Wieringa, R. (2013b): Ontological Distinctions between Means-End and Contribution Links in the i* Framework, 32nd International Conference on Conceptual Modeling (ER 2013), Hong Kong.
78. Guizzardi, R.S.S., Guizzardi, G. (2010): Ontology-based transformation framework from tropos to AORML, in: *Social Modeling for Requirements Engineering*, in: *Cooperative Information Systems Series*, MIT Press, Boston.
79. Halpin, T. (2010): Object-Role Modeling: Principles and Benefits, *International Journal of Information Systems Modeling and Design*, Vol. 1, No. 1, IGI Global, pp. 32-54.
80. Halpin, T. & Morgan T. (2008): *Information Modeling and Relational Databases*, 2nd edition, Morgan Kaufmann.
81. Heller, B., Herre, H. (2004): Ontological Categories in GOL. *Axiomathes* 14: 71-90 Kluwer Academic Publishers.
82. Heller, B., Herre, H., Burek, P., Loebe, F., Michalek, H. (2004): General Ontology Language (GOL) – A Formal Framework for Building and Representing Ontologies, *Onto-Med Report*, Nr. 7. Research Group

Ontologies in Medicine, University of Leipzig.

83. Henderson-Sellers, B. et al. (2014): An ontology for ISO software engineering standards: 1) Creating the infrastructure. *Computer Standards & Interfaces* 36(3): 563-576.
84. Hitchman, S. (2003): An interpretive study of how practitioners use entity-relationship modeling in a ternary relationship situation, *Comm. Assoc. for Inf. Systems*, 11, 451-485.
85. Kent, W. (1978): *Data and Reality*, Elsevier Science.
86. Masolo, C.; Borgo, S.; Gangemi, A.; Guarino, N.; Oltramari, A. (2003): *Ontology Library*, WonderWeb Deliverable D18.
87. Masolo, C.; Guizzardi, G.; Vieu, L.; Bottazzi, E.; Ferrario, R. (2005): *Relational Roles and Qua Individuals*, AAAI Fall Symposium on Roles, an Interdisciplinary Perspective, Virginia, USA.
88. Mealy, G. H. (1967) *Another Look at Data*, AFIPS Conference Proceedings, Volume 31, Washington, DC: Thompson Books, London: Academic Press, 525-534.
89. Moreira et al. (2014): *OntoWarehousing - Multidimensional Design Supported by a Foundational Ontology: A Temporal Perspective*, *Data Warehousing and Knowledge Discovery*, *Lecture Notes in Computer Science* Volume 8646, pp 35-44.
90. Moreira, J. et al. (2015): *Developing Situation-Aware Applications for Disaster Management with a Distributed Rule-Based Platform*, *Proceedings of the RuleML 2015 Doctoral Consortium 9th International Web Rule Symposium (RuleML 2015)*, Berlin.
91. Moretto, C., Barcellos, M.P. (2014): *A Levels-based Approach for Defining Software Measurement Architectures*, *CLEI Electronic Journal*, vol.17 no.3 Montevideo.
92. Mylopoulos, J., *Conceptual modeling and Telos* (1992): In P. Loucopoulos & R. Zicari (eds.), *Conceptual Modeling, Databases, and CASE* (Chapter 2, pp. 49-68). Wiley.
93. Nardi, J. C., de Almeida Falbo, R., Almeida, J. P. A., Guizzardi, G., Pires, L. F., van Sinderen, M. J., Guarino, N., Fonseca, C. M. (2015): *A Commitment-based Reference Ontology for Services*, *Information Systems*, Elsevier.
94. Nijenhuis, C. F. (2011): *Automatic generation of graphical domain ontology editors*, University of Twente.
95. Nunes, R.P., et al. (2015): *Measurement Ontology Pattern Language Applied to Network Performance Measurement*, *Brazilian Seminar on Ontological Research (Ontobras 2015)*, São Paulo, Brazil, 2015.
96. Olivé, A. (2007): *Conceptual Modeling of Information Systems*. Springer.
97. Parsons, T. (1990): *Events in the Semantics of English: A Study in Subatomic Semantics*, MIT Press, Cambridge, MA.
98. Pereira, L.D., Calhau, R.F., Santos Junior, P. S., Costa, M.B. (2015): *Ontologia de Domínio de Doação de Órgãos e Tecidos para apoio a Integração Semântica de Sistemas (A Domain Ontology for Organ and Tissue Donation and its Support for Semantic System Integration)*, 18th Ibero-American Conference on Software Engineering (CibSE 2015).
99. Pergl, R., Sales, T.P., Rybola, Z. (2013): *Towards OntoUML for Software Engineering: from Domain Ontology to Implementation Model, Model and Data Engineering*, Volume 8216 of the series *Lecture Notes in Computer Science* pp 249-263.
100. Ruy, F.B., Reginato, C.C., Santos, V.A., Falbo, R. de A., Guizzardi, G. (2015): *Ontology Engineering by Combining Ontology Patterns*. 34th International Conference on Conceptual Modeling (ER'2015). , Stockholm, Sweden.
101. Salles, T.P., Guizzardi, G. (2015): *Ontological Anti-Patterns: Empirically Uncovered Error-Prone Structures in Ontology-Driven Conceptual Models*, *Data & Knowledge Engineering (DKE) Journal*, Elsevier.
102. Santos Junior, P. S., Almeida, J.P.A., Guizzardi, G. (2013): *An Ontology-Based Analysis and Semantics for Organizational Structure Modeling in the ARIS Method*. *Information Systems* (Oxford).
103. Santos, Jr., P.S.; Almeida, J.P.A.; Guizzardi, G. (2010): *An Ontology-Based Semantic Foundation for ARIS EPCs*, 25th ACM Symposium On Applied Computing (ACM SAC 2010), Sierre, Switzerland.
104. Serra, S.M.S.C., et al. (2012): *A Foundational Ontology to Support Scientific Experiments*, *Proceedings of Joint V Seminar on Ontology Research in Brazil and VII International Workshop on Metamodels, Ontologies and Semantic Technologies*.
105. Shekhovtsov, V.A., Mayr, H.C. (2014): *Managing Quality Related Information in Software Development Processes*, *Proceedings of the CAiSE 2014 Forum*, 26th International Conference on Advanced Information Systems Engineering (CAiSE 2014), Thessaloniki, Greece, June 18-20.
106. U.S. Department of Defense (2011): *Data Modeling Guide (DMG) for an Enterprise Logical Data Model (ELDM)*, available online: http://www.omgwiki.org/architecture-ecosystem/lib/exe/fetch.php?media=dmg_for_enterprise_ldm_v2_3.pdf.
107. Veres, C.; Hitchman, S. (2002): *Using Psychology to Understand Conceptual Modeling*, 10th European Conference on Information Systems (ECIS 2002), Poland.
108. Veres, C.; Mansson, G. (2005): *Cognition and Modeling: Foundations for Research and Practice*, *Journal of Information Technology Theory and Application*, v.7, n.1, 93-10.
109. Wand Y., Storey V.C., Weber R. (1999): *An ontological analysis of the relationship construct in conceptual modeling*, *ACM Trans. on Database Systems*, 24(4):494-528. Dec.
110. Wand, Y. & Weber, R. (1989). *An ontological evaluation of systems analysis and design methods*. In Falkenberg, E.D. & Lindgreen, P. (eds.), *Information System Concepts: An In-depth Analysis*, North-

Holland.

111. Wand, Y., Weber, R. (1990): An Ontological Model of an Information System. *IEEE Trans. Software Eng.* 16(11): 1282-1292.
112. Weber, R. (1997): *Ontological Foundations of Information Systems*, Coopers & Lybrand, Melbourne.
113. Weber, R., Zhang, Y., (1991): An Ontological Evaluation of NIAM's Grammar for Conceptual Schema Diagrams " (1991). *ICIS 1991 Proceedings*. Paper 48.
114. Werlang, R. (2015): *Ontology-based approach for standard formats integration in reservoir modeling*, M.Sc. Thesis, Federal University of Rio Grande do Sul.
115. Zamborlini, Guizzardi, G. (2010): On the representation of temporally changing information in OWL, in: *15th IEEE International Enterprise Computing Conference (EDOC 2010) Workshop Proceedings*, Vitória, Brazil.